

SHUTTLE™ 2+2 OPTIONS & ACCESSORIES

APPEARANCE	
Vehicle Color	<ul style="list-style-type: none"> • Almond • Bright White • Burgundy • Black • Electric Blue • Flame Red • Forest Green • Inferno Red • Ivory • Patriot Blue • Platinum • Steel Blue (custom colors available)
Seat Color	<ul style="list-style-type: none"> • Stone Beige • Ivory (custom colors available)
Weather Protection	<ul style="list-style-type: none"> • Sun Canopy: Stone Beige, Oyster • 3-Sided Weather Enclosure • Windshield: Flat, Fold Down
ELECTRICAL	
Battery Charger (electric only)	<ul style="list-style-type: none"> • 48 V PowerWise™ with 18 foot DC Cord
Other Electrical	<ul style="list-style-type: none"> • CE Kit (electric only) • Heavy-Duty Batteries (Trojan T-1275) (electric only) • Turn Signals • Brake Lights • Hour Meter
TIRES AND WHEELS	
Tires	<ul style="list-style-type: none"> • T-Shot 18 x 8.50-8 • Tour Max 18 x 8.50-10 on Alloy Wheels
Wheel Covers	<ul style="list-style-type: none"> • Platinum Spoke
PERFORMANCE	
Other Options/Accessories	<ul style="list-style-type: none"> • Two-Bag Carrier • Ash Tray • Glove Box Doors, Driver and Passenger • Message Holder



PLATINUM WHEEL COVERS



The E-Z-GO® Shuttle™ 2+2 is designed to deliver the style and comfort your guests expect and the efficiency and reliability you demand. Whether it's the electric model with its innovative AC Drive and full-time regenerative braking system, or the gas-powered model with its best-in-class 13 hp Kawasaki® engine, the Shuttle 2+2 is well equipped to smoothly transport up to four passengers.

EXCELLENCE IN MOTION



A Textron Company

1451 Marvin Griffin Road, Augusta, GA 30906 | (706) 796-4311
 Fax (706) 796-4540 | (800) 241-5855 | www.ezgo.com
 e-mail: ezgo@textron.com | ©2008 E-Z-GO Division of Textron Inc.



822015-G3



SHUTTLE™ 2+2

ELECTRIC

BODY & CHASSIS	
Frame	Welded steel with DuraShield™ epoxy coating
Body & Finish	Injection-molded TPO
Standard Color	Forest Green
DIMENSIONS	
Overall Length	106.0 in (269 cm)
Overall Width	47.0 in (119 cm)
Overall Height (no canopy)	45.7 in (116 cm) (top of steering wheel)
Overall Height (with canopy)	68.5 in (174 cm) (top of sun canopy)
Wheel Base	65.7 in (167 cm)
Front Wheel Track	35.5 in (90 cm)
Rear Wheel Track	38.0 in (97 cm)
Ground Clearance (at differential)	4.5 in (11 cm)
POWER	
Power Source	48-volt DC
Motor Type	48-volt AC
Horsepower (kW)	4.4 hp (3.3 kW) continuous
Electric System	48-volt
Batteries (qty/type)	Four, 12-volt deep cycle
Battery Charger	48 V Delta-Q high frequency, UL and CSA
Speed Controller	230 amp AC controller with 3.0 hp output
Drive Train	Motor shaft direct drive
Transaxle	Limited slip differential
Gear Selection	Key switch
Rear Axle Ratio	16.99:1
PERFORMANCE	
Seating Capacity	4-person
Dry Weight (without batteries)	539 lb (244 kg)
Curb Weight	887 lb (402 kg)
Vehicle Load Capacity	800 lb (360 kg)



SIDE

PERFORMANCE (CONT.)	
Outside Clearance Circle	19.2 ft (5.8 m)
Ground Speed (level ground)	14.5 mph ± 0.5 mph (23 kph ± 0.8 kph)
STEERING & SUSPENSION	
Steering	Double-ended rack and pinion
Front Suspension	Independent A-arm coilover shock
Rear Suspension	Mono-leaf spring with hydraulic shocks
Service Brake	Electric motor
Parking Brake	Automatic electro-magnetic
Front Tires	Turf 18 x 8.50-8 (4-ply rated)
Rear Tires	Turf 18 x 8.50-8 (4-ply rated)
OTHER STANDARD FEATURES	
Front and Rear Energy Transfer Bumpers, Headlights, Taillights, Horn, Ergonomically Designed Center Console with Multiple Cup Holders, State of Charge Meter	



FRONT



BACK

GAS

BODY & CHASSIS	
Frame	Welded steel with DuraShield™ epoxy coating
Body & Finish	Injection-molded TPO
Standard Color	Forest Green
DIMENSIONS	
Overall Length	106.0 in (269 cm)
Overall Width	47.0 in (119 cm)
Overall Height (no canopy)	45.7 in (116 cm) (top of steering wheel)
Overall Height (with canopy)	68.5 in (174 cm) (top of sun canopy)
Wheel Base	65.7 in (167 cm)
Front Wheel Track	35.5 in (90 cm)
Rear Wheel Track	38.0 in (97 cm)
Ground Clearance (at differential)	3.3 in (11 cm)
POWER	
Power Source	4-cycle 24.5 cu in (401 cc) low emissions
Valve Train	Single cylinder OHV
Horsepower (kW)	13 hp (9.7 kW) exceeds SAE J1940 standard
Electric System	Starter/generator, solid state regulator
Batteries (qty/type)	One, 12-volt maintenance-free
Air Cleaner	Remote intake, industrial-rated dry filter
Lubrication	Pressurized oil system
Oil Filter	Spin on
Cooling System	Air-cooled
Fuel Capacity	6.2 gallon (23.5 L)
Drive Train	Automatic, continuously variable transmission (CVT)
Transaxle	Differential with helical gears
Gear Selection	Forward-reverse
Rear Axle Ratio	11.42:1 (Forward) 15.78:1 (Reverse)

PERFORMANCE	
Seating Capacity	4-person
Dry Weight (without batteries)	867 lb (393 kg)
Curb Weight	917 lb (416 kg)
Vehicle Load Capacity	800 lb (360 kg)
Outside Clearance Circle	19.0 ft (5.8 m)
Ground Speed (level ground)	14.5 mph ± 0.5 mph (23 kph ± 0.8 kph)
STEERING & SUSPENSION	
Steering	Double-ended rack and pinion
Front Suspension	Independent A-arm coilover shock
Rear Suspension	Mono-leaf spring with hydraulic shocks
Service Brake	Rear wheel mechanical self-adjusting drums
Parking Brake	Self-compensating, single point engagement
Front Tires	Turf 18 x 8.50-8 (4-ply rated)
Rear Tires	Turf 18 x 8.50-8 (4-ply rated)
OTHER STANDARD FEATURES	
Front and Rear Energy Transfer Bumpers, Headlights, Taillights, Horn, Ergonomically Designed Center Console with Multiple Cup Holders, Fuel Meter	

To learn more about the Shuttle 2+2™ or to receive a custom quote, please call: (800) 241-5855 or visit www.ezgo.com.